

View Online at <https://aerobasegroup.com/nsn/4720-00-606-9483>

Cross Sectional Shape:

Round

Thread Class:

2a 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.187 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Outside Diameter:

Between 0.359 inches and 0.391 inches

Connection Style:

Swivel nut, inverted flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external tube 2nd end

Thready Qty Per Inch (tpi):

24 2nd end

Burst Test Pressure:

1700.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and outer layer rubber impregnated braided rayon cord

Maximum Operating Pressure:

425.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

84.0 degrees 2nd end

Hydrostatic Test Pressure:

850.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and fuel resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

17.000 inches

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Uns 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0