

View Online at <https://aerobasegroup.com/nsn/4720-00-608-6313>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

1.811 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

**Flange Thickness:**

0.300 inches 2nd end

**Outside Diameter:**

2.090 inches

**Minimum Inside Bending Radius:**

17.000 inches

**Center To Center Distance Between Bolt Holes Along Width:**

2.380 inches 2nd end

**Center To Center Distance Between Bolt Holes Along Length:**

2.380 inches 2nd end

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

3.000 inches 2nd end

**Flange Width:**

3.000 inches 2nd end

**Connection Style:**

Raised 2nd end

**Bolt Hole Diameter:**

0.270 inches 2nd end

**Raised Face Height:**

0.010 inches and 0.020 inches 2nd end

**Raised Face Diameter:**

2.750 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Raised face flange 2nd end

**Burst Test Pressure:**

500.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated cotton fabric

**Maximum Operating Pressure:**

125.0 pounds per square inch

**Hydrostatic Test Pressure:**

250.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

12.060 inches

**Flange Style:**

Rectangular (includes square) 2nd end

**Special Features:**

Second end has a second 90 degrees angle to right as viewed from second end

**Media For Which Designed:**

Fuel/oil, hydrocarbon single response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0