

View Online at <https://aerobasegroup.com/nsn/4720-00-608-6313>

Cross Sectional Shape:

Round

Inside Diameter:

1.811 inches

Temperature Rating:

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Flange Thickness:

0.300 inches 2nd end

Outside Diameter:

2.090 inches

Minimum Inside Bending Radius:

17.000 inches

Center To Center Distance Between Bolt Holes Along Width:

2.380 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.380 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

3.000 inches 2nd end

Flange Width:

3.000 inches 2nd end

Connection Style:

Raised 2nd end

Bolt Hole Diameter:

0.270 inches 2nd end

Raised Face Height:

0.010 inches and 0.020 inches 2nd end

Raised Face Diameter:

2.750 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Raised face flange 2nd end

Burst Test Pressure:

500.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided wire and outer layer rubber impregnated cotton fabric

Maximum Operating Pressure:

125.0 pounds per square inch

Hydrostatic Test Pressure:

250.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

12.060 inches

Flange Style:

Rectangular (includes square) 2nd end

Special Features:

Second end has a second 90 degrees angle to right as viewed from second end

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0