Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-609-2306

Bross Gettoring Graph. Round Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.188 inches Tempurature Rating: -57.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.312 inches Minimu Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 2000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1200.0.0 pounds per square inch Layer Composition And Location: Outer Layer braided corrosion resistant steel wire Maximum Operating Pressure: 1200.0.0 pounds per square inch Hread Size: 0.438 inches 1st end Set Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: <t< th=""><th>Cross Sectional Shape:</th><th></th></t<>	Cross Sectional Shape:	
Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.188 inches Tempurature Rating: -6.7.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.312 inches Minimum Inside Bending Radius: 2.000 inches Connection Dstyle: 2.000 inches Connection Dstyle: Siviel nut flare 2nd end End Connection Design: Straight 1st end Connection Dstyle: Straight 1st end Connection Dstyle: Straight 1st end Connection Dstyle: Straight 1st end Connection Dstyle: Straight 1st end Connection Design: Straight 1st end Connection Style: Straight 1st end Straight 1st end Connection Design: Straight 1st end Straight 1st end Straight 1st end Straight 1st end Connection page square inch Straight 1st end Straight 1st end St		
Strate and Strate and Thread Direction: Right-hand 1st end Inside Diameter: 0.188 Inches Tempurature Rating: 67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.312 Inches Minimun Inside Bending Radius: 2.000 Inches Connection Style: Swivel nut flare 2nd end End Connection Design: Strate and Outside Diameter: 0.300 Inches Connection Design: Strate and Data and the st end Dometion Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 130.0 opunds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 030.0 pounds per square inch Flow Angle:		
Thread Direction: Right-hand 1st end Inside Diameter: 0.188 inches Tempurature Rating: -87.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.312 inches Minimun Inside Bending Radius: 2.000 inches Connection Style: 2.000 inches Connection Design: Straight 1st end Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 300.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Hydrostatic Test Pressure: 300.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Murster Corrosion resistant Flow Angle: 45.0 degrees 2nd end Murster Corrosion resistant Flow Angle: 45.0 degrees 2nd end Murster Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 30.8 Inside Surface Condition: Smoth Measuring Method And Length:		
Right-hand 1st end Inside Diameter: 0.188 inches Tempurature Rating: -67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.312 inches Minimun Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximun Operating Pressure: 1900.0 pounds per square inch Straight 1st end Austinches 1st end Burst Test Pressure: 1900.0 pounds per square inch Hared Condition: 1900.0 pounds per square inch Burst Test Pressure: 1900.0 pounds per square inch Burder Stered 1900.0 pounds per square inch Burder Stered 1900.0 pounds per square inch Burder Stered 1900.0 pounds per		
Inside Diameter: 0.188 inches Tempurature Rating: -67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.312 inches Minimun Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 150.0 pounds per square inch Thread Size: 0.438 linches 1st end State Angle: 300.0 pounds per square inch Hydrostatic Test Pressure: 160.00 pounds per square inch Furead Size: 0.438 linches 1st end State Angle: 300.0 pounds per square inch Flow Angle: 420 degrees 2nd end Hydrostatic Test Pressure: 300.0 gounds per square inch Flow Angle:		
Name 0.188 inches Tempurature Rating: -67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.312 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threade internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Steat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.4		
Tempurture Rating: -67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.312 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Design: Straight 1st end Connection Type: Threade internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Set Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Mydrostatic Test Pressure: 300.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Mydrostatic Test Pressure: 50.8 Inside Surface Condition: Soure In Torr: 50.8 Inside Surface Condition: Smouth Measuring Method And Length:		
-67.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response Outside Diameter: 0.312 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Maxeuring Method And Length:		
Outside Diameter: 0.312 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 300.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Maximus Method And Length:		
0.312 inches Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Mur Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:		
Minimum Inside Bending Radius: 2.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Minimum Pressure: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:		
2.000 inches Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Muter Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth		
Connection Style: Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:		
Swivel nut flare 2nd end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth		
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth	-	
Straight 1st end Connection Type: Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth		
Answer Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Mage Subord	-	
Threaded internal tube 1st end Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth	-	
Burst Test Pressure: 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Yacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:		
 12000.0 pounds per square inch Layer Composition And Location: Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length: 		
Layer Composition And Location:Outer layer braided corrosion resistant steel wireMaximum Operating Pressure:1500.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchFlow Angle:45.0 degrees 2nd endOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:SmoothMeasuring Method And Length:		
Outer layer braided corrosion resistant steel wire Maximum Operating Pressure: 1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:		
Maximum Operating Pressure:1500.0 pounds per square inchThread Size:0.438 inches 1st endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchFlow Angle:45.0 degrees 2nd endOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:SmoothMaximum Method And Length:		
1500.0 pounds per square inch Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:		
Thread Size:0.438 inches 1st endSeat Angle:37.0 degrees 2nd endHydrostatic Test Pressure:3000.0 pounds per square inchFlow Angle:45.0 degrees 2nd endOuter Covering Environmental Protection:Corrosion resistantVacuum In Torr:50.8Inside Surface Condition:SmoothMeasuring Method And Length:		
0.438 inches 1st end Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:	1500.0 pounds per square inch	
Seat Angle: 37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:	Thread Size:	
37.0 degrees 2nd end Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:	0.438 inches 1st end	
Hydrostatic Test Pressure: 3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:	Seat Angle:	
3000.0 pounds per square inch Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:	37.0 degrees 2nd end	
Flow Angle: 45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:	Hydrostatic Test Pressure:	
45.0 degrees 2nd end Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:	3000.0 pounds per square inch	
Outer Covering Environmental Protection: Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:	Flow Angle:	
Corrosion resistant Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:	45.0 degrees 2nd end	
Vacuum In Torr: 50.8 Inside Surface Condition: Smooth Measuring Method And Length:	Outer Covering Environmental Protection:	
50.8 Inside Surface Condition: Smooth Measuring Method And Length:	Corrosion resistant	
Inside Surface Condition: Smooth Measuring Method And Length:	Vacuum In Torr:	
Smooth Measuring Method And Length:	50.8	
Measuring Method And Length:	Inside Surface Condition:	
	Smooth	
18.250 inches working	Measuring Method And Length:	
	18.250 inches working	

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Unjf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0