

View Online at <https://aerobasegroup.com/nsn/4720-00-609-8686>

Cross Sectional Shape:

Round

Thread Class:

2b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.688 inches

Minimum Inside Bending Radius:

4.000 inches

Exterior Color:

Black

Hose Or Tubing Specification/std Data:

Mil-h-8795 jamil-h-8795 size 10 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Socket steel 2nd end

Fitting Component And Surface Treatment:

Socket cadmium 2nd end

Connection Type:

Threaded internal tube 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

20000.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

2nd layer braided steel wire

Maximum Operating Pressure:

5000.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

10000.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.000 inches and 21.500 inches

Special Features:

Inner conveying tube material-rubber, synthetic; one protective guard to secure hose

Media For Which Designed:

Air and fuel/oil, hydrocarbon and water single response

Thread Series Designator:

Unf 1st end

Specification Data:

Mil-h-8795 jamil-h-8795 size 10 professional/industrial association specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-8795 spec.