## NSN 4720-00-613-7268



Nonmetallic Hose Assembly - Page 1 of 2	AGI UD 45 Group
View Online at https://aerobasegroup.com/nsn/4720-00-613-7268	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Tempurature Rating:	
-565.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response	
Outside Diameter:	
0.312 inches	
Minimum Inside Bending Radius:	
2.000 inches	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability and reusable end fittings	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
1500.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 2nd end	
Hydrostatic Test Pressure:	
3000 0 pounds per square inch	

Flow Angle:

90.0 degrees 2nd end

**Outer Covering Environmental Protection:** 

Corrosion resistant

Vacuum In Torr:

50.8

**Inside Surface Condition:** 

Smooth

## NSN 4720-00-613-7268

Nonmetallic Hose Assembly - Page 2 of 2



Measuring	Method	And	Length:
-----------	--------	-----	---------

29.000 inches working

**Thread Series Designator:** 

Unjf 1st end

**Specification Data:** 

96906-ms8000 government standard

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0