Nonmetallic Hose Assembly - Page 1 of 2



resistant steel wire

View Online at https://aerobasegroup.com/nsn/4720-00-615-2093

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.344 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.547 inches
Minimum Inside Bending Radius:
2.500 inches
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
6000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
14.000 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response

Nonmetallic Hose Assembly - Page 2 of 2



**Thread Series Designator:** 

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0