Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-618-7394

C	Cross Sectional Shape:
F	Round
Т	hread Class:
3	b 1st end
Т	Thread Direction:
F	Right-hand 1st end
h	nside Diameter:
B	Between 0.300 inches and 0.346 inches
Т	empurature Rating:
-(65.0 degrees fahrenheit single response and 500.0 degrees fahrenheit single response
C	Dutside Diameter:
B	Between 0.430 inches and 0.471 inches
N	/inimum Inside Bending Radius:
2	2.100 inches
E	Exterior Color:
Ν	latural
С	Connection Style:
F	lare 2nd end
E	Ind Connection Design:
S	Straight 2nd end
C	Connection Type:
Т	Threaded internal tube 1st end
Т	hready Qty Per Inch (tpi):
1	8 1st end
E	Burst Test Pressure:
3	000.0 pounds per square inch
L	ayer Composition And Location:
C	Duter layer braided corrosion resistant steel wire
N	laximum Operating Pressure:
1	25.0 pounds per square inch
Т	hread Size:
0	.562 inches 2nd end
S	Seat Angle:
3	7.0 degrees 2nd end
H	lydrostatic Test Pressure:
2	00.0 pounds per square inch
F	low Angle:
9	0.0 degrees 1st end
h	nside Surface Condition:
S	Smooth
N	leasuring Method And Length:
1	5.600 inches working

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:

Unf 2nd end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0