NSN 4720-00-618-7814

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-618-7814

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.344 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 158.0 degrees fahrenheit single response
Outside Diameter:
0.766 inches
Connection Style:
Swivel nut with compression sleeve 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and outer layer molded rubber, synthetic
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 1st end
Seat Angle:
12.0 degrees 1st end
Hydrostatic Test Pressure:
7000.0 pounds per square inch
7000.0 pounds per square inch Inside Surface Condition:
Inside Surface Condition:
Inside Surface Condition: Smooth
Inside Surface Condition: Smooth Measuring Method And Length:
Inside Surface Condition: Smooth Measuring Method And Length: 15.625 inches working
Inside Surface Condition: Smooth Measuring Method And Length: 15.625 inches working Media For Which Designed:
Inside Surface Condition: Smooth Measuring Method And Length: 15.625 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response
Inside Surface Condition: Smooth Measuring Method And Length: 15.625 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator:
Inside Surface Condition: Smooth Measuring Method And Length: 15.625 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unf 1st end

N/a

NSN 4720-00-618-7814

Nonmetallic Hose Assembly - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A542a0