NSN 4720-00-618-9019

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-618-9019

| Cross Sectional Shape: |
|--|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.250 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.688 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Inverted flare 1st end |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Complete fitting steel all ends |
| Connection Type: |
| Threaded external pipe 1st end |
| Second End Relationship With First End: |
| Identical |
| identical |
| Burst Test Pressure: |
| |
| Burst Test Pressure: |
| Burst Test Pressure: 20000.0 pounds per square inch |
| Burst Test Pressure: 20000.0 pounds per square inch First End Swivel Action Capability: |
| Burst Test Pressure: 20000.0 pounds per square inch First End Swivel Action Capability: Not included |
| Burst Test Pressure: 20000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: |
| Burst Test Pressure: 20000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer sheet rubber |
| Burst Test Pressure: 20000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer sheet rubber Maximum Operating Pressure: |
| Burst Test Pressure: 20000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer sheet rubber Maximum Operating Pressure: 5000.0 pounds per square inch |
| Burst Test Pressure: 20000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer sheet rubber Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: |
| Burst Test Pressure: 20000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer sheet rubber Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: 0.250 inches 1st end |
| Burst Test Pressure: 20000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer sheet rubber Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: |
| Burst Test Pressure: 20000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer sheet rubber Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end |
| Burst Test Pressure: 20000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer sheet rubber Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: |
| Burst Test Pressure: 20000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer sheet rubber Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 10000.0 pounds per square inch |
| Burst Test Pressure: 20000.0 pounds per square inch First End Swivel Action Capability: Not included Layer Composition And Location: 1st layer sheet rubber Maximum Operating Pressure: 5000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 30.0 degrees 1st end Hydrostatic Test Pressure: 10000.0 pounds per square inch Inside Surface Condition: |

Special Features:

Inner conveying tube material-rubber, synthetic

NSN 4720-00-618-9019

Nonmetallic Hose Assembly - Page 2 of 2



| Media | For | Which | Design | ed |
|-------|-----|-------|--------|----|
| | | | | |

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0