NSN 4720-00-620-5662

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-620-5662

View Online at https://aerobasegroup.com/nsn/4720-00-620-5662
Cross Sectional Shape:
Round
Inside Diameter:
0.750 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.250 inches
Minimum Inside Bending Radius:
9.500 inches
Angle Between Rigid Elbow Fittings In Deg:
0.0
Flange Outside Diameter:
1.500 inches 1st end
Connection Style:
Plain w/ gasket groove (sae flanged head) 1st end
End Flange Construction:
Solid 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Plain face flange 1st end
Burst Test Pressure:
9000.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic and 1st layer rubber impregnated braided steel wire and 3rd layer braided cotton cord
Maximum Operating Pressure:
2250.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.500 inches working
Flange Style:
Round w/ out bolt holes 1st end
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:

N/a

NSN 4720-00-620-5662

Nonmetallic Hose Assembly - Page 2 of 2



		• .					
	In	iŧ	Of	MAG	200		ω.
•	,,,	ıL	v.	IAIC	as	u	┏.

--

Demilitarization:

No

Fiig:

A542a0