Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-622-1594

#### **Cross Sectional Shape:**

Round

**Thread Class:** 

3b 1st end

## **Thread Direction:**

Right-hand 1st end

#### Inside Diameter:

0.250 inches

#### **Tempurature Rating:**

-65.0 degrees fahrenheit and 158.0 degrees fahrenheit single response

#### **Outside Diameter:**

0.500 inches

#### Minimum Inside Bending Radius:

4.000 inches

#### Hose Or Tubing Specification/std Data:

Mil mil-h-5593, size no. 4 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### First End Fitting Specification/std Data:

Mil ms27404-4d standard (includes industry or association standards, individual manufactureer standards, etc.).

## **Connection Style:**

Swivel nut flare 1st end

### End Connection Design:

Straight 1st end

#### **Connection Type:**

Threaded internal tube 1st end

### Second End Relationship With First End:

Identical

### Burst Test Pressure:

1250.0 pounds per square inch

### First End Swivel Action Capability:

Not included

### Layer Composition And Location:

Outer layer molded rubber

### First End Fitting/component And Material:

Complete fitting-aluminum alloy, qq-a-225/5, alloy 2017, t4 or qq-a-225/6, alloy 2024, t351 or t4 or qq-a-367, alloy 2014, t4

### **Maximum Operating Pressure:**

200.0 pounds per square inch

## Thread Size:

0.438 inches 1st end

#### Seat Angle:

37.0 degrees 1st end

### Hydrostatic Test Pressure:

400.0 pounds per square inch

Nonmetallic Hose Assembly - Page 2 of 2



# Outer Covering Environmental Protection:

Incombustible

### Vacuum In Torr:

508.0

# Inside Surface Condition:

Smooth

## Measuring Method And Length:

20.000 inches working

## **Special Features:**

Inner conveying tube material-rubber, synthetic; complete fitting-aluminum alloy, qq-a-225/5, alloy 2017, t4 or qq-a-225/6, alloy 2024, t351

or t4 or qq-a-367, alloy 2014, t4

### Media For Which Designed:

Fuel/oil, hydrocarbon single response

## **Thread Series Designator:**

Unf 1st end

### Shelf Life:

N/a

## Unit Of Measure:

---

### Demilitarization:

No

## Fiig:

A542a0