NSN 4720-00-623-8017

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-623-8017

Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
Between 0.735 inches and 0.781 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response	
Outside Diameter:	
1.190 inches	
Minimum Inside Bending Radius:	
9.500 inches	
Exterior Color:	
Black	
Connection Style:	
Inverted flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded external pipe 1st end	
Burst Test Pressure:	
9000.0 pounds per square inch	
Layer Composition And Location:	
1st layer braided wire and 2nd layer braided wire and outer layer molde	d rubber, synthetic
Maximum Operating Pressure:	
2250.0 pounds per square inch	
Thread Size:	
0.750 inches 1st end	
Seat Angle:	
30.0 degrees 1st end	
Hydrostatic Test Pressure:	
4500.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
28.250 inches	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Npt 1st end	
Shelf Life:	
N/a	

NSN 4720-00-623-8017

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0