

View Online at <https://aerobasegroup.com/nsn/4720-00-624-4060>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

3.000 inches

**Temperature Rating:**

-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response

**Outside Diameter:**

3.594 inches

**Minimum Inside Bending Radius:**

33.000 inches

**Features Provided:**

Electrostatic discharge capability

**Burst Test Pressure:**

800.0 pounds per square inch single response

**Layer Composition And Location:**

3rd layer braided cotton cord err-100

**Maximum Operating Pressure:**

200.0 pounds per square inch single response

**Hydrostatic Test Pressure:**

400.0 pounds per square inch single response

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and mildew resistant

**Vacuum In Torr:**

457.2

**Inside Surface Condition:**

Smooth

**Material:**

Rubber synthetic tube

**Media For Which Designed:**

Hydraulic fluid, phosphate-ester base single response and hydraulic fluid, silicate-ester base single response and gas, natural single response and oil, lubricating, diester base single response and air single response and water, fresh single response and water, salt single response

**Specification Data:**

81343-sae j517, 100r5 government standard

**Specification Or Standard:**

48 size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A541z0

**Mil-std (military Standard):**

Mil-h-24135 spec.