Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-625-0305

| Cross Sectional Shape: |
|---|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.500 inches |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.780 inches |
| Minimum Inside Bending Radius: |
| 6.000 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut, gasket seal 1st end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal hose 1st end |
| Thready Qty Per Inch (tpi): |
| 11-1/2 2nd end |
| Burst Test Pressure: |
| 750.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided rayon cord and outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch |
| Thread Size: |
| 0.750 inches 2nd end |
| Hydrostatic Test Pressure: |
| 250.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 300.000 inches |
| Media For Which Designed: |
| Water single response |
| Thread Series Designator: |
| Nh 2nd end |
| Shelf Life: |
| N/a |
| |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0