

View Online at <https://aerobasegroup.com/nsn/4720-00-625-2355>

Cross Sectional Shape:

Round

Inside Diameter:

1.000 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Flange Thickness:

0.370 inches and 0.380 inches 1st end

Outside Diameter:

1.656 inches

Recess Diameter:

1.500 inches 1st end

Recess Depth:

0.385 inches and 0.395 inches 1st end

Minimum Inside Bending Radius:

13.000 inches

Flange Outside Diameter:

2.250 inches 1st end

Connection Style:

Recessed 1st end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer braided wire and 2nd layer braided wire and 3rd layer braided wire and 4th layer braided cotton cord and outer layer molded rubber, synthetic

Maximum Operating Pressure:

3000.0 pounds per square inch

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

30.0 degrees 2nd end

Outer Covering Environmental Protection:

Abrasion resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

20.562 inches working

Flange Style:

Round w/ out bolt holes 2nd end

Media For Which Designed:

Hydraulic fluid single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0