NSN 4720-00-626-0142

Cross Sectional Shape:

Round

Thread Class: 2b 1st end

Thread Direction: Right-hand 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-626-0142

Inside Diameter:
0.125 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 450.0 degrees fahrenheit 1st response
Outside Diameter:
0.250 inches
Minimum Inside Bending Radius:
1.500 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
End Fitting Component And Material:
Complete fitting stainless steel all ends
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
14.625 inches working
Special Features:
Inner conveying tube material-plastic, polytetrafluoroethylene
Thread Series Designator:
Unf 1st end

NSN 4720-00-626-0142

Nonmetallic Hose Assembly - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0