NSN 4720-00-626-7377

Thread Class:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-626-7377

Cross Sectional Shape:
Round

| 3b all ends |
|---|
| Thread Direction: |
| Right-hand all ends |
| Inside Diameter: |
| 0.188 inches |
| Outside Diameter: |
| 0.313 inches |
| Minimum Inside Bending Radius: |
| 4.000 inches |
| Connection Style: |
| Swivel nut flare all ends |
| End Connection Design: |
| Straight 1st end |
| End Fitting Component And Material: |
| Nut aluminum alloy all ends |
| Connection Type: |
| Threaded internal tube all ends |
| Burst Test Pressure: |
| 9000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer rubber impregnated braided corrosion resistant stee |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 0.438 inches 1st end |
| Seat Angle: |
| 37.0 degrees all ends |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 25.375 inches working |
| Material Specification: |
| Amil-h-5511a military specification all material responses tube |
| Thread Series Designator: |
| Unf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

wire

NSN 4720-00-626-7377

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | | | |
|----|-----|---------|-----|---|--|
| 11 | em) | tor | 172 | n | |
| | | | | | |

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-5511a spec.