

View Online at <https://aerobasegroup.com/nsn/4720-00-626-7394>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.875 inches

Temperature Rating:

Not rated

Outside Diameter:

1.031 inches

Minimum Inside Bending Radius:

9.000 inches

First End Connection Type:

Threaded internal tube

First End Thread Class:

3b

First End Thread Direction:

Right-hand

First End Seat Angle In Deg:

37.0

First End Connection Design:

Straight

Hose Or Tubing Specification/std Data:

Mil-h-5511a specification

First End Fitting Specification/std Data:

Ms33656-16 standard

Connection Style:

Swivel nut flare 1st end

End Fitting Component And Material:

Nut aluminum alloy all ends

Fitting Component And Surface Treatment:

Nut cadmium 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Second End Relationship With First End:

Identical

Burst Test Pressure:

4200.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer rubber impregnated braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

First End Thready Qty Per Inch (tpi):

12

First End Thread Series Designator:

Un

Seat Angle:

37.0 degrees 1st end

First End Thread Size:

1.312 inches

Inside Surface Condition:

Smooth

Measuring Method And Length:

16.000 inches working

Special Features:

Inner conveying tube material-plastic, polytetrafluoroethylene

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-5511 spec.