Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-626-8074

С	cross Sectional Shape:
R	Round
Т	hread Class:
3	b 1st end
Т	hread Direction:
R	light-hand 1st end
Ir	nside Diameter:
0	.437 inches
Т	empurature Rating:
-6	65.0 degrees fahrenheit and 400.0 degrees fahrenheit single response
С	Dutside Diameter:
0	.687 inches
С	Connection Style:
S	wivel nut flare 1st end
E	nd Connection Design:
S	straight 1st end
С	Connection Type:
Т	hreaded internal tube 1st end
В	Burst Test Pressure:
1	4.000 pounds per square inch
L	ayer Composition And Location:
1	st layer braided steel wire and outer layer braided corrosion resistant steel wire
N	faximum Operating Pressure:
3	000.0 pounds per square inch
т	hread Size:
0	.750 inches 1st end
S	eat Angle:
3	7.0 degrees 1st end
Н	lydrostatic Test Pressure:
3	000.0 pounds per square inch
N	leasuring Method And Length:
1	7.250 inches working
т	hread Series Designator:
U	Inf 1st end
S	shelf Life:
N	I/a
U	Init Of Measure:
D	Demilitarization:
N	lo
F	iig:
	.542a0