

View Online at <https://aerobasegroup.com/nsn/4720-00-627-9964>

Cross Sectional Shape:

Round

Inside Diameter:

2.375 inches

Width Across Flats:

4.000 inches 1st end

Temperature Rating:

-65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

Bolt Circle Diameter:

3.812 inches 1st end

Flange Thickness:

0.188 inches 2nd end

Outside Diameter:

2.695 inches

Minimum Inside Bending Radius:

24.000 inches

Angle Between Rigid Elbow Fittings In Deg:

229.0

Center To Center Distance Between Bolt Holes Along Width:

2.375 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.375 inches 2nd end

Bolt Hole Quantity:

6 1st end

Flange Length:

3.000 inches 2nd end

Flange Width:

3.000 inches 2nd end

Connection Style:

Raised swivel 2nd end

Bolt Hole Diameter:

0.328 inches 2nd end

Raised Face Height:

0.015 inches 2nd end

Raised Face Diameter:

2.750 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Raised face flange 2nd end

Features Provided:

Reusable end fittings

Burst Test Pressure:

560.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

120.0 pounds per square inch

Hydrostatic Test Pressure:

240.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

41.380 inches working

Flange Style:

Rectangular (includes square) 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0