NSN 4720-00-628-0575

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-628-0575

Cross Sectional Shape:					
Round					
Thread Class:					
2a 1st end					
Thread Direction:					
Right-hand 1st end					
Inside Diameter:					
0.250 inches					
Tempurature Rating:					
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response					
Outside Diameter:					
0.445 inches					
Minimum Inside Bending Radius:					
3.000 inches					
Exterior Color:					
Black					
Connection Style:					
Swivel nut, inverted flare 1st end					
End Connection Design:					
Straight 1st end					
Connection Type:					
Threaded external tube 1st end					
Thready Qty Per Inch (tpi):					
24 1st end					
Burst Test Pressure:					
1000.0 pounds per square inch					
Layer Composition And Location:					
1st layer braided synthetic cord and outer layer molded rubber, synthetic					
Maximum Operating Pressure:					
250.0 pounds per square inch					
Thread Size:					
0.438 inches 1st end					
Seat Angle:					
37.0 degrees 1st end					
Hydrostatic Test Pressure:					
500.0 pounds per square inch					
Inside Surface Condition:					
Smooth					
Measuring Method And Length:					
58.504 inches					

Media For Which Designed:

Fuel/oil, hydrocarbon single response

NSN 4720-00-628-0575

Nonmetallic Hose Assembly - Page 2 of 2



Th.		Carias	Dania	
1111	reau	Series	Desig	mator.

Uns 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0