## NSN 4720-00-628-6591

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-628-6591 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.219 inches **Tempurature Rating:** -67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response **Outside Diameter:** 0.469 inches **Connection Style:** Swivel nut, inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Electrostatic discharge capability **Burst Test Pressure:** 16000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided steel wire and 2nd layer molded polytetrafluoroethylene and outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 3000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 12.0 degrees 1st end **Hydrostatic Test Pressure:** 6000.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 9.625 inches working **Thread Series Designator:** Unf 1st end Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 4720-00-628-6591

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0