Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-628-6592

Cross Sectional Shape	:
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.219 inches	
Tempurature Rating:	
-65.0 degrees fahrenhei	and 400.0 degrees fahrenheit single response
Outside Diameter:	
).469 inches	
Minimum Inside Bendi	ng Radius:
3.000 inches	
Connection Style:	
Swivel nut, flareless 1st	end
End Connection Desig	n:
Straight 1st end	
Connection Type:	
Threaded internal tube 1	st end
Features Provided:	
Electrostatic discharge of	apability
Burst Test Pressure:	
16000.0 pounds per squ	are inch
Layer Composition An	d Location:
1st layer spirally laid ste	el wire and 2nd layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided corrosion resistant
steel wire	
Maximum Operating P	ressure:
3000.0 pounds per squa	re inch
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Press	ure:
6000.0 pounds per squa	re inch
Inside Surface Conditi	on:
Smooth	
Measuring Method And	I Length:
9.875 inches working	
Thread Series Designa	tor:
Unf 1st end	
Shelf Life:	
N/a	

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0