NSN 4720-00-630-5096

Cross Sectional Shape:

Unf 1st end

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-630-5096

Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.406 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response				
Outside Diameter:				
0.562 inches				
Minimum Inside Bending Radius:				
4.620 inches				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Features Provided:				
Electrostatic discharge capability				
Burst Test Pressure:				
8000.0 pounds per square inch				
Layer Composition And Location:				
Outer layer braided corrosion resistant steel wire				
Maximum Operating Pressure:				
1500.0 pounds per square inch				
Thread Size:				
0.750 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
3000.0 pounds per square inch				
Vacuum In Torr:				
50.8				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
7.875 inches working				
Thread Series Designator:				

NSN 4720-00-630-5096

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

07482-102a136+080077 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0