NSN 4720-00-630-5100

Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-630-5100

Round
Thread Class:
3b 2nd end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.500 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.656 inches
Angle Between Rigid Elbow Fittings In Deg:
305.0
Connection Style:
Swivel nut flare 2nd end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 2nd end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
7000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.875 inches 2nd end
Seat Angle:
37.0 degrees 2nd end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Inside Surface Condition:
Smooth
Measuring Method And Length:
9.500 inches working
Thread Series Designator:
Unf 2nd end

NSN 4720-00-630-5100

Nonmetallic Hose Assembly - Page 2 of 2



Specific	ation	Data:
----------	-------	-------

24446-r213+100094c305 manufacturers specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0