Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-630-5921

Round Thread Class: 3b 1st and Thread Direction: Right-hand 1st and Inside Diameter: 0.438 inches Tempurature Rating: 65.0 degrees fahrenheit and 120.0 degrees fahrenheit single response Outside Diameter: 0.435 inches Minimum Inside Bending Radius: 5.750 inches Exterior Color: Black Connection Style: Strivel nut flate 1st end Exterior Color: Phreade linternal tube 1st end Factorenotrype: Threaded linternal tube 1st end Factorenotrype: Threaded linternal tube 1st end Factores Provide: Resusable end fittings Butt Butt 1st end Stel wire and 2nd layer braided stel wire and outer layer molded rubber, chloroprene Noto, pounds per square inch Layer Strippe Stel and Douto pounds per square inch Layer Composition And Legits	
Sub Steind Thread Direction: Right-hand 1st end Inside Diameter: 0.438 inches Tempurature Rating: -65.0 degrees fahrenheit and 120.0 degrees fahrenheit single response Outside Diameter: 0.438 inches Minimun Inside Bending Radius: 5.750 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Burt 1st end Layer Composition And Location: 14000.0 pounds per square inch Layer Composition And Location: 0.750 inches 1st end Set Angle: 0.750 inches 1st end Facture Covering Environmental Protection: Onto pounds per square inch Layer Covering Environment	Round
Thread Direction: Right-hand 1st end Inside Diameter: 0.438 inches Tempurture Rating: -65.0 degrees fahrenheit and 120.0 degrees fahrenheit single response Outside Diameter: 0.859 inches Minimum Inside Bending Radius: 6.750 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Peaters Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Miximum Operating Pressure: 3000.0 pounds per square inch Marcia Size 0.750 inches 1st end Parced Composition And Location: 14000.0 pounds per square inch Marcia Direction Pressure: 3000.0 pounds per square inch Marcia Directions Pressure: 3000.0 pounds per square inch Hered Size 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 70.0 degrees 1st end	Thread Class:
Right-hand 1st end Inside Diameter: 0.438 inches Tempurture Rating: -65.0 degrees fahrenheit and 120.0 degrees fahrenheit single response Outside Diameter: 0.859 inches Minimu Inside Bending Radius: 5.750 inches Exterior Color: Black Connection Dsign: Straight 1st end Connection Design: Straight 1st end Featers Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 15.750 inches 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 0.750 inches 1st end Straiget 1st end Here State Joudoup per square inch Here Composition And Location: 14000.0 pounds per square inch Here Composition And Location: 0.750 inches 1st end	3b 1st end
Iside Diameter: 0.438 inches Tempurature Rating: -65.0 degrees fahrenheit and 120.0 degrees fahrenheit single response Outside Diameter: 0.859 inches Minimun Inside Bending Radius: 5.750 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end Enconnection Design: Straight 1st end Connection Type: Threaded linemal tube 1st end Factures Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Straight 1st end Chreed Steel 900.0 pounds per square inch Straight 1st end 900.0 pounds per square inch	Thread Direction:
0.438 inchesTempurature Rating:- 65.0 degrees fahrenheit and 120.0 degrees fahrenheit single responseOutside Diameter:0.859 inchesMinimul Inside Bending Radius:5.750 inchesExterior Color:BlackConnection Style:Swivel nut flare 1st endEndconnection Design:Straight 1st endForeaction Type:Threaded internal tube 1st endFatures Provided:Reusable end fittingsBurst Test Pressure:14000.0 pounds per square inchLayer Composition And Location:3000.0 pounds per square inchExterior Size:0.750 inches 1st endHorread Size:0.700 opounds per square inchHarread Size:0.750 inches 1st endHorread Size:0.750 inches 1st endHydrostatic Test Pressure:0.700.0 pounds per square inchHydrostati Test Pressure:1700.0 pounds per square inch </td <td>Right-hand 1st end</td>	Right-hand 1st end
Tempuraure Rating: -65.0 degrees fahrenheit and 120.0 degrees fahrenheit single response Outside Diameter: 0.859 inches Minimum Inside Bending Radius: 5.750 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Hydrostatic Test Pressure: 37.0 degrees 1st end Hydrostatic Test Pressure: 37.0 degrees 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smooth	Inside Diameter:
b5.0 degrees fahrenheit and 120.0 degrees fahrenheit single responseCutside Diameter:0.859 inchesMinimun Inside Bending Radius:5.750 inchesExterior Color:BlackConnection Style:Swivel nut flare 1st endEnd Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFatures Provided:Reusable end fittingsBurst Test Pressure:14000.0 pounds per square inchLayer Composition And Location:Notion Statisht 1st endStraight 1st endSurger Statisht 1st endBurst Test Pressure:14000.0 pounds per square inchLayer Composition And Location:1510:0 pounds per square inchStraight 1st endStraight 1st endConcettin Stressure:1000:0 pounds per square inchLayer Composition And Location:1710:0 pounds per square inchStraight 1st endStraight 1st endStressure:100:0 pounds per square inchStraight 1st endStraight 1st endSt	0.438 inches
Outside Diameter:0.859 inchesMinimun Inside Bending Radius:5.750 inchesExterior Color:BlackConnection Style:Swivel nut flare 1st endEndocation Style:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Reusable end fittingsBurst Test Pressure:14000.0 pounds per square inchLayer Composition And Location:15t layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloropreneMaximum Operating Pressure:3000.0 pounds per square inchEntered Size:0.750 inches 1st endFread Size:0.750 inches 1st endStraiget 1st endChreed Size:0.750 inches 1st endMaximum Operating Pressure:0.750 inches 1st endHydrostatic Test Pressure:0.750 inches 1st endStraigetStraiget 1st endHydrostatic Test Pressure:0.750 inches 1st endHydrostatic Test Pressure:1700.0 pounds per square inchHydrostatic Test Pressure:1700.0 pounds per square inch<	Tempurature Rating:
0.859 inches Minimu Inside Bending Radius: 5.750 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Factures Provided: Reusable end fittings Bust 14000.0 pounds per square inch Layer Composition And Location: 13000.0 pounds per square inch Maximum Operating Pressure: 0.750 inches 1st end 9000.0 pounds per square inch Hardes 14000 pounds per square inch 17000 pounds per square inch	-65.0 degrees fahrenheit and 120.0 degrees fahrenheit single response
Minimu Inside Bending Radius: 5.750 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 13t layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Exteres Steel 7.700.0 pounds per square inch Extere Steel 7.700.0 pounds per square inch Exteres Steel Fortower Steel 7.700.0 pounds per square inch Exteres Steel Fortower Steel 7.700.0 pounds per square inch Exteres Steel Fortower Steel <	Outside Diameter:
S.750 inches Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene 3000.0 pounds per square inch Hread Size: 3000.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Hydrostatic Test Pressure: Ab	0.859 inches
Exterior Color: Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Dure Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smoth Measuring Method And Length:	Minimum Inside Bending Radius:
Black Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 141ser Pressure: 1000.0 pounds per square inch Extreme Size: 1750 inches 1st end 2750 inches 1st end 9400.0 pounds per square inch 1750 inches 1st end 970.0 pounds per square inch 1760.0 pounds per square inch 970.0 inches 1st end 970.0 inches 1st end 970.0 pounds per square inch 1770 inches 1st end 970.0 inches 1st end 970.0 pounds per square inch	5.750 inches
Connection Style: Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 141st end Straight st end 2000.0 pounds per square inch Maximum Operating Pressure: 3000.0 pounds per square inch Streed Size: 0.750 inches 1st end Seet Angle: 97.0 degrees 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Durd Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smoth Measuring Method And Length:	Exterior Color:
Swivel nut flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Dure Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smoth	Black
End Connection Design:Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Reusable end fittingsBurst Test Pressure:14000.0 pounds per square inchLayer Composition And Location:1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:7000.0 pounds per square inchDirect Covering Environmental Protection:Abrasion resistant and oil resistantInside Surface Condition:SinothHydrostati And Location:SinothSinothStraige Stat and Stat Stat Stat Stat Stat Stat Stat Sta	Connection Style:
Straight 1st endConnection Type:Threaded internal tube 1st endFeatures Provided:Reusable end fittingsBurst Test Pressure:14000.0 pounds per square inchLayer Composition And Location:1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloropreneMaximum Operating Pressure:3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:7000.0 pounds per square inchDuter Covering Environmental Protection:Abrasion resistant and oil resistantInside Surface Condition:SmothMesuring Method And Length:	Swivel nut flare 1st end
Year Preaded internal tube 1st end Features Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Duret Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smooth	End Connection Design:
Threaded internal tube 1st end Features Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Cuter Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smooth Keasuring Method And Length:	Straight 1st end
Features Provided: Reusable end fittings Burst Test Pressure: 14000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	Connection Type:
Reusable end fittingsBurst Test Pressure:14000.0 pounds per square inchLayer Composition And Location:1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloropreneMaximum Operating Pressure:3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:7000.0 pounds per square inchCuter Covering Environmental Protection:Abrasion resistant and oil resistantInside Surface Condition:SmothMeasuring Method And Length:	Threaded internal tube 1st end
Burst Test Pressure:14000.0 pounds per square inchLayer Composition And Location:1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloropreneMaximum Operating Pressure:3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:7000.0 pounds per square inchDuter Covering Environmental Protection:Abrasion resistant and oil resistantInside Surface Condition:SmothMeasuring Method And Length:	Features Provided:
 14000.0 pounds per square inch Layer Composition And Location: 1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene Maximum Operating Pressure: 3000.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length: 	Reusable end fittings
Layer Composition And Location:1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloropreneMaximum Operating Pressure:3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:7000.0 pounds per square inchOuter Covering Environmental Protection:Abrasion resistant and oil resistantInside Surface Condition:SmoothMeasuring Method And Length:	Burst Test Pressure:
Ast layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloropreneMaximum Operating Pressure:3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:7000.0 pounds per square inchOuter Covering Environmental Protection:Abrasion resistant and oil resistantInside Surface Condition:SmoothMeasuring Method And Length:	14000.0 pounds per square inch
Maximum Operating Pressure:3000.0 pounds per square inchThread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:7000.0 pounds per square inchOuter Covering Environmental Protection:Abrasion resistant and oil resistantInside Surface Condition:SmoothMeasuring Method And Length:	Layer Composition And Location:
3000.0 pounds per square inch Thread Size: 0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene
Thread Size:0.750 inches 1st endSeat Angle:37.0 degrees 1st endHydrostatic Test Pressure:7000.0 pounds per square inchOuter Covering Environmental Protection:Abrasion resistant and oil resistantInside Surface Condition:SmoothMeasuring Method And Length:	Maximum Operating Pressure:
0.750 inches 1st end Seat Angle: 37.0 degrees 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	3000.0 pounds per square inch
Seat Angle:37.0 degrees 1st endHydrostatic Test Pressure:7000.0 pounds per square inchOuter Covering Environmental Protection:Abrasion resistant and oil resistantInside Surface Condition:SmoothMeasuring Method And Length:	Thread Size:
37.0 degrees 1st end Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	0.750 inches 1st end
Hydrostatic Test Pressure: 7000.0 pounds per square inch Outer Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	Seat Angle:
7000.0 pounds per square inch Outer Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	37.0 degrees 1st end
Outer Covering Environmental Protection: Abrasion resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	Hydrostatic Test Pressure:
Abrasion resistant and oil resistant Inside Surface Condition: Smooth Measuring Method And Length:	7000.0 pounds per square inch
Inside Surface Condition: Smooth Measuring Method And Length:	Outer Covering Environmental Protection:
Smooth Measuring Method And Length:	Abrasion resistant and oil resistant
Measuring Method And Length:	Inside Surface Condition:
	Smooth
49.000 inches	Measuring Method And Length:
	49.000 inches



Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0