

View Online at <https://aerobasegroup.com/nsn/4720-00-630-7558>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.625 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Outside Diameter:

0.781 inches

Center To Center Distance Between Bolt Holes Along Width:

1.156 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.156 inches 2nd end

Bolt Hole Quantity:

4 1st end

Connection Style:

Swivel nut flare 1st end

Bolt Hole Diameter:

0.205 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Electrostatic discharge capability

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

1.062 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

29.750 inches working

Flange Style:

Rectangular (includes square) 2nd end

Special Features:

Polytetrafluoroethylene external support

Thread Series Designator:

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0