Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-631-3942

-		<b>.</b> .
Cross	Sectional	Shape:

Round

**Thread Direction:** 

Right-hand 1st end

# Inside Diameter:

0.250 inches

# **Outside Diameter:**

0.453 inches

# **Connection Style:**

Plain 2nd end

## End Connection Design:

Straight 2nd end

#### Connection Type:

Threaded external hose 2nd end

#### Thready Qty Per Inch (tpi):

27 2nd end

#### Burst Test Pressure:

1250.0 pounds per square inch

# Layer Composition And Location:

1st layer braided cotton cord and outer layer molded rubber

# Maximum Operating Pressure:

300.0 pounds per square inch

# Thread Size:

0.250 inches 1st end

#### Hydrostatic Test Pressure:

625.0 pounds per square inch

## **Outer Covering Environmental Protection:**

Fuel resistant and mildew resistant and oil resistant and ozone resistant

# Inside Surface Condition:

Smooth

## Measuring Method And Length:

11.000 inches

## Media For Which Designed:

Fuel/oil, hydrocarbon single response

#### **Thread Series Designator:**

Unf 1st end

Shelf Life:

N/a

# Unit Of Measure:

--

# Demilitarization:

No

# NSN 4720-00-631-3942

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

