

View Online at <https://aerobasegroup.com/nsn/4720-00-636-8044>

Cross Sectional Shape:

Round

Inside Diameter:

0.625 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Flange Thickness:

0.297 inches 2nd end

Outside Diameter:

0.781 inches

Center To Center Distance Between Bolt Holes Along Width:

1.156 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.156 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

1.594 inches 2nd end

Flange Width:

1.594 inches 2nd end

Connection Style:

Plain swivel 2nd end

Bolt Hole Diameter:

0.205 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Straight 1st end

Connection Type:

Plain face flange 2nd end

Features Provided:

Electrostatic discharge capability

Burst Test Pressure:

6000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

28.000 inches working

Flange Style:

Rectangular (includes square) 2nd end

Specification Data:

24446-102a140+120280 manufacturers source control

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0