NSN 4720-00-639-9988

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-639-9988 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** Between 0.172 inches and 0.204 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 212.0 degrees fahrenheit single response **Outside Diameter:** Between 0.391 inches and 0.438 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 700.0 pounds per square inch **Layer Composition And Location:** 1st layer braided cotton cord and outer layer molded rubber Thread Size: 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 350.0 pounds per square inch **Outer Covering Environmental Protection:** Fire retardant and oil resistant Vacuum In Torr:

254.0 **Inside Surface Condition:** Smooth **Measuring Method And Length:** 8.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end Shelf Life: N/a

NSN 4720-00-639-9988

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0