## NSN 4720-00-640-6404

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-640-6404 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.219 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response **Outside Diameter:** 0.438 inches **Minimum Inside Bending Radius:** 2.000 inches **Exterior Color:** Natural **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 6000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided corrosion resistant steel wire, partial coverage and outer layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1000.0 pounds per square inch **Thread Size:** 0.438 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 3000.0 pounds per square inch **Outer Covering Environmental Protection:** Corrosion resistant **Vacuum In Torr:** 76.2 **Inside Surface Condition:** 

Smooth

**Measuring Method And Length:** 

12.500 inches working

## NSN 4720-00-640-6404

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unjf 1st end
Specification Data:
96906-ms87028e124a government specification
Specification Or Standard:
4 size
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0