

View Online at <https://aerobasegroup.com/nsn/4720-00-651-0856>

Cross Sectional Shape:

Round

Inside Diameter:

1.125 inches

Temperature Rating:

-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response

Flange Thickness:

0.234 inches 1st end

Outside Diameter:

1.359 inches

Minimum Inside Bending Radius:

11.000 inches

Angle Between Rigid Elbow Fittings In Deg:

45.0

Center To Center Distance Between Bolt Holes Along Width:

1.656 inches 1st end

Center To Center Distance Between Bolt Holes Along Length:

1.656 inches 1st end

Bolt Hole Quantity:

4 1st end

Flange Length:

2.188 inches 1st end

Flange Width:

2.188 inches 1st end

Connection Style:

Raised 1st end

Bolt Hole Diameter:

0.266 inches 1st end

Raised Face Height:

0.030 inches 1st end

Raised Face Diameter:

1.854 inches 1st end

End Flange Construction:

Solid 1st end

End Connection Design:

Elbow 1st end

Connection Type:

Raised face flange 1st end

Burst Test Pressure:

4000.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1000.0 pounds per square inch

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Flow Angle:

90.0 degrees 1st end

Inside Surface Condition:

Smooth

Measuring Method And Length:

27.750 inches working

Flange Style:

Rectangular (includes square) 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0