## NSN 4720-00-651-0856

**Cross Sectional Shape:** 

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-651-0856

Inside Diameter:
1.125 inches
Tempurature Rating:
-100.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Flange Thickness:
0.234 inches 1st end
Outside Diameter:
1.359 inches
Minimum Inside Bending Radius:
11.000 inches
Angle Between Rigid Elbow Fittings In Deg:
45.0
Center To Center Distance Between Bolt Holes Along Width:
1.656 inches 1st end
Center To Center Distance Between Bolt Holes Along Length:
1.656 inches 1st end
Bolt Hole Quantity:
4 1st end
Flange Length:
2.188 inches 1st end
Flange Width:
2.188 inches 1st end
Connection Style:
Raised 1st end
Bolt Hole Diameter:
0.266 inches 1st end
Raised Face Height:
0.030 inches 1st end
Raised Face Diameter:
1.854 inches 1st end
End Flange Construction:
Solid 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Raised face flange 1st end
Burst Test Pressure:
4000.0 pounds per square inch

Outer layer braided corrosion resistant steel wire

**Layer Composition And Location:** 

## NSN 4720-00-651-0856

Nonmetallic Hose Assembly - Page 2 of 2



Maximum Operating Pressure:
1000.0 pounds per square inch
Hydrostatic Test Pressure:
2000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
27.750 inches working
Flange Style:
Rectangular (includes square) 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A542a0