NSN 4720-00-658-2324

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-658-2324

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.219 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.625 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided wire and 2nd layer braided wire and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Outer Covering Environmental Protection:
Fuel resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
16.000 inches working

Fuel/oil, hydrocarbon single response

Media For Which Designed:

NSN 4720-00-658-2324

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator
Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0