## NSN 4720-00-658-5261

**Cross Sectional Shape:** 

Round

**Thread Class:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-658-5261

3b 1st end						
Thread Direction:						
Right-hand 1st end						
Inside Diameter:						
0.188 inches						
Tempurature Rating:						
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response						
Outside Diameter:						
0.312 inches						
Connection Style:						
Swivel nut flare 2nd end						
End Connection Design:						
Straight 1st end						
Connection Type:						
Threaded internal tube 1st end						
Features Provided:						
Electrostatic discharge capability						
Thready Qty Per Inch (tpi):						
20 2nd end						
Burst Test Pressure:						
12000.0 pounds per square inch						
Layer Composition And Location:						
Outer layer braided corrosion resistant steel wire						
Maximum Operating Pressure:						
1500.0 pounds per square inch						
Thread Size:						
0.438 inches 1st end						
Seat Angle:						
37.0 degrees 2nd end						
Hydrostatic Test Pressure:						
3000.0 pounds per square inch						
Flow Angle:						
90.0 degrees 2nd end						
Inside Surface Condition:						
Smooth						
Measuring Method And Length:						
9.625 inches working						
Special Features:						
Polytetrafluoroethylene external support						

## NSN 4720-00-658-5261

Nonmetallic Hose Assembly - Page 2 of 2



	••		•	_		
ı	hre	ลด	Seri	26 I I	PSIU	nator:
•		uu	CCII		COIG	mator.

Unf 2nd end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0