NSN 4720-00-659-6967

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-659-6967 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.750 inches **Minimum Inside Bending Radius:** 5.000 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** 1st layer braided wire and outer layer molded rubber, synthetic **Maximum Operating Pressure:** 2250.0 pounds per square inch **Thread Size:** 0.625 inches 2nd end Seat Angle: 45.0 degrees 2nd end **Hydrostatic Test Pressure:** 4500.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end **Measuring Method And Length:** 72.000 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 2nd end

Shelf Life:

N/a

NSN 4720-00-659-6967

Nonmetallic Hose Assembly - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A542a0