

View Online at <https://aerobasegroup.com/nsn/4720-00-670-1168>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.875 inches

**Temperature Rating:**

-100.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

**Flange Thickness:**

0.234 inches 2nd end

**Outside Diameter:**

1.109 inches

**Minimum Inside Bending Radius:**

7.375 inches

**Angle Between Rigid Elbow Fittings In Deg:**

350.0

**Center To Center Distance Between Bolt Holes Along Width:**

1.312 inches 2nd end

**Center To Center Distance Between Bolt Holes Along Length:**

1.312 inches 2nd end

**Bolt Hole Quantity:**

4 2nd end

**Flange Length:**

1.750 inches 2nd end

**Flange Width:**

1.750 inches 2nd end

**Connection Style:**

Raised 2nd end

**Bolt Hole Diameter:**

0.205 inches 2nd end

**Raised Face Height:**

0.030 inches 2nd end

**Raised Face Diameter:**

1.510 inches 2nd end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Elbow 2nd end

**Connection Type:**

Raised face flange 2nd end

**Burst Test Pressure:**

5000.0 pounds per square inch

**Layer Composition And Location:**

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1250.0 pounds per square inch

**Hydrostatic Test Pressure:**

2500.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

21.000 inches

**Flange Style:**

Rectangular (includes square) 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0