

View Online at <https://aerobasegroup.com/nsn/4720-00-670-1168>

Cross Sectional Shape:

Round

Inside Diameter:

0.875 inches

Temperature Rating:

-100.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

Flange Thickness:

0.234 inches 2nd end

Outside Diameter:

1.109 inches

Minimum Inside Bending Radius:

7.375 inches

Angle Between Rigid Elbow Fittings In Deg:

350.0

Center To Center Distance Between Bolt Holes Along Width:

1.312 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

1.312 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

1.750 inches 2nd end

Flange Width:

1.750 inches 2nd end

Connection Style:

Raised 2nd end

Bolt Hole Diameter:

0.205 inches 2nd end

Raised Face Height:

0.030 inches 2nd end

Raised Face Diameter:

1.510 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Raised face flange 2nd end

Burst Test Pressure:

5000.0 pounds per square inch

Layer Composition And Location:

1st layer braided corrosion resistant steel wire and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

1250.0 pounds per square inch

Hydrostatic Test Pressure:

2500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.000 inches

Flange Style:

Rectangular (includes square) 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0