NSN 4720-00-674-4491

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-674-4491

The Common at International States of the Common of the Co				
Cross Sectional Shape:				
Round				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.250 inches				
Tempurature Rating:				
-65.0 degrees fahrenheit and 50.0 degrees fahrenheit single response				
Outside Diameter:				
0.625 inches				
Minimum Inside Bending Radius:				
4.000 inches				
Connection Style:				
Plain optional end 1st end				
End Connection Design:				
Straight 2nd end				
Connection Type:				
Threaded internal pipe 1st end				
Burst Test Pressure:				
11000.0 pounds per square inch				
Layer Composition And Location:				
1st layer braided steel wire and outer layer molded rubber, chloroprene				
Maximum Operating Pressure:				
2750.0 pounds per square inch				
Thread Size:				
0.125 inches 2nd end				
Seat Angle:				
30.0 degrees 2nd end				
Hydrostatic Test Pressure:				
5500.0 pounds per square inch				
Outer Covering Environmental Protection:				
Oil resistant and ozone resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
14.750 inches				
Thread Series Designator:				
Nptf 2nd end				
Specification Data:				
81349-mil-h-13531 government specification				
Shelf Life:				
N/				

N/a

NSN 4720-00-674-4491

Nonmetallic Hose Assembly - Page 2 of 2



П	Init	7 1+	Measure:
u	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	v	wicasuic.

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13531 spec.