

View Online at <https://aerobasegroup.com/nsn/4720-00-674-9139>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.375 inches

Temperature Rating:

-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response

Flange Thickness:

0.312 inches 2nd end

Outside Diameter:

1.750 inches

Minimum Inside Bending Radius:

11.000 inches

Exterior Color:

Black

Angle Between Rigid Elbow Fittings In Deg:

270.0

Center To Center Distance Between Bolt Holes Along Width:

2.000 inches 2nd end

Center To Center Distance Between Bolt Holes Along Length:

2.000 inches 2nd end

Bolt Hole Quantity:

4 2nd end

Flange Length:

2.562 inches 2nd end

Flange Width:

2.562 inches 2nd end

Connection Style:

Swivel nut flare 1st end

Bolt Hole Diameter:

0.344 inches 2nd end

End Flange Construction:

Solid 2nd end

End Connection Design:

Elbow 2nd end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

1st layer braided cotton cord and 2nd layer braided steel wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

50.0 pounds per square inch

Thread Size:

1.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

600.0 pounds per square inch

Flow Angle:

45.0 degrees 1st end

Outer Covering Environmental Protection:

Alcohol resistant and cold resistant and oil resistant and water resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

32.625 inches working

Flange Style:

Rectangular (includes square) 2nd end

Special Features:

Fittings color coded mil-f-5509

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0