Metallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-675-6547

Round Thread Class: 2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Dutside Diameter: 0.250 inches Inner Conveying Tube Style: Interlocked unpacked Exterior Color: Gold Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end End Connection Design: Straight 1st end End Connection Type: Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 800.0 pounds per square inch Thread Size: 1.250 inches 1st end Seat Angle: 40.0 degrees 1st end Seat Angle: 10.1 Streid Size: 11.5 Shirt Life: Na Unit 1st end Shirt Life: Na Shirt Life: Na Shirt Life: Na Shirt Life: Na <t< th=""><th>Cross Sectional Shape:</th><th></th></t<>	Cross Sectional Shape:	
2b 1st end Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Dutside Diameter: 0.250 inches Inner Conveying Tube Style: Interfocked unpacked Exterior Color: Gold Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Thread de internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Douter layer braided bronze wire Maximum Operating Pressure: B000.0 pounds per square inch Thread Size: D.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Und 1st end Shelf Life: Na Unit Of Measure: Thread Series Designator: Unit 1st end Shelf Life: Na Dinth	Round	
Thread Direction: Right-hand 1st end Inside Diameter: 0.250 inches Outside Diameter: 0.250 inches Inner Conveying Tube Style: Interlocked unpacked Exterior Color: Gold Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Thread el internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 1.250 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: Na Unf 1st end Shelf Life: Na	Thread Class:	
Right-hand 1st end Inside Diameter: 0.250 inches Outside Diameter: 0.250 inches Inner Conveying Tube Style: Inner Conveying Tube Style: Interlocked unpacked Exterior Color: Gold Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 8000.0 pounds per square inch Thread Size: 0.250 inches and 72.500 inches Thread Series Designator: Und 1st end Shelf Life: Na Unit of Measure: Pomilitarization: No Fig:	2b 1st end	
Inside Diameter: 0.250 inches Dutside Diameter: 0.250 inches Inner Conveying Tube Style: Interlocked unpacked Exterior Color: Gold Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Douter layer braided bronze wire Maximum Operating Pressure: 8000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: Na Unit of Measure: Demilitarization: No Fig:	Thread Direction:	
Inside Diameter: 0.250 inches Dutside Diameter: 0.250 inches Inner Conveying Tube Style: Interlocked unpacked Exterior Color: Gold Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Douter layer braided bronze wire Maximum Operating Pressure: 8000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: Na Unit of Measure: Demilitarization: No Fig:	Right-hand 1st end	
Duside Diameter: Duside Diameter: Duside Diameter: Duside Diameter: Duside Diameter: Duside Diameter: Duside Diameter: Duside Diameter: Diameter: Duside Diameter: Dia	Inside Diameter:	
D.250 inches Inner Conveying Tube Style: Interlocked unpacked Exterior Color: Gold Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threade internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unit 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.250 inches	
Inner Conveying Tube Style: Interlocked unpacked Exterior Color: Gold Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Outside Diameter:	
Interlocked unpacked Exterior Color: Gold Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.250 inches	
Exterior Color: Gold Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Seat Angle: 40.0 degrees 1st end Massuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit of Measure: - Demilitarization: No Filg:	Inner Conveying Tube Style:	
Gold Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Interlocked unpacked	
Connection Style: Inverted flare 1st end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Exterior Color:	
Inverted flare is end End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Duter layer braided bronze wire Maximum Operating Pressure: B000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Size: Unf 1st end Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	Gold	
End Connection Design: Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Connection Style:	
Straight 1st end Connection Type: Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Inverted flare 1st end	
Conection Type: Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	End Connection Design:	
Threaded internal tube 1st end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Straight 1st end	
Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Connection Type:	
Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	Threaded internal tube 1st end	
Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Features Provided:	
Outer layer braided bronze wire Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Identical ends	
Maximum Operating Pressure: 6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Layer Composition And Location:	
6000.0 pounds per square inch Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Outer layer braided bronze wire	
Thread Size: 0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Maximum Operating Pressure:	
0.250 inches 1st end Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	6000.0 pounds per square inch	
Seat Angle: 40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	Thread Size:	
40.0 degrees 1st end Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	0.250 inches 1st end	
Measuring Method And Length: 71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No	Seat Angle:	
71.500 inches and 72.500 inches Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	40.0 degrees 1st end	
Thread Series Designator: Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Measuring Method And Length:	
Unf 1st end Shelf Life: N/a Unit Of Measure: Demilitarization: No Filg:	71.500 inches and 72.500 inches	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	Thread Series Designator:	
N/a Unit Of Measure: Demilitarization: No Filg:	Unf 1st end	
Unit Of Measure: Demilitarization: No Filg:	Shelf Life:	
 Demilitarization: No Fiig:	N/a	
Demilitarization: No Fiig:	Unit Of Measure:	
No Fiig:		
Fiig:	Demilitarization:	
-	No	
A542a0	Fiig:	
	A542a0	