NSN 4720-00-676-7050

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-676-7050

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.690 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
1.862 inches
Minimum Inside Bending Radius:
14.000 inches
Exterior Color:
Black
Connection Style:
Plain optional end 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal pipe 1st end
Thready Qty Per Inch (tpi):
14 1st end
Burst Test Pressure:
2000.0 pounds per square inch
Layer Composition And Location:
1st layer spiral interlocked steel and outer layer spirally wrapped cotton duck, rubber impregnated
Maximum Operating Pressure:
500.0 pounds per square inch
Thread Size:
0.750 inches 2nd end
Hydrostatic Test Pressure:
1000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.750 inches
Special Features:
3/4 in. Tapped union nipple, part no. 544810 fscm 82722 on one end
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:

Npt 1st end

NSN 4720-00-676-7050

Nonmetallic Hose Assembly - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J			_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0