Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-677-0653

Cross Sectional Shape: Round Thread Class: 3b 1st end Thread Direction: Right-hand 1st end Inside Diameter:	
Thread Class: 3b 1st end Thread Direction: Right-hand 1st end	
3b 1st end Thread Direction: Right-hand 1st end	
Thread Direction: Right-hand 1st end	
Right-hand 1st end	
-	
Inside Diameter:	
0.312 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response	
Outside Diameter:	
0.627 inches	
Minimum Inside Bending Radius:	
4.000 inches	
Connection Style:	
Swivel nut flare 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Burst Test Pressure:	
9000.0 pounds per square inch	
_ayer Composition And Location:	
Ist layer braided cotton cord and 2nd layer rubber impregnated braided steel wire and outer layer rubber impregnated braided cottor	cord
Maximum Operating Pressure:	
2000.0 pounds per square inch	
Thread Size:	
0.562 inches 1st end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
4500.0 pounds per square inch	
Vacuum In Torr:	
50.8	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
12.000 inches	
Media For Which Designed:	
Air and alcohol, ethyl and fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Unjf 1st end	

NSN 4720-00-677-0653

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

