## NSN 4720-00-678-0100

**Cross Sectional Shape:** 

Round

Thread Class: 2a 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.250 inches

**Tempurature Rating:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-678-0100

-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response

Outside Diameter:
Between 0.562 inches and 0.625 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Black
Connection Style:
Plain 2nd end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
1000.0 pounds per square inch
Layer Composition And Location:
1st layer rubber impregnated cotton fabric and outer layer rubber impregnated fabric
Maximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
42.0 degrees 1st end
Hydrostatic Test Pressure:
500.0 pounds per square inch
Outer Covering Environmental Protection:
Mildew resistant and oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
6.625 inches
Media For Which Designed:
Alcohol, ethyl and ethylene glycol and fuel/oil, hydrocarbon and water, fresh single response

## NSN 4720-00-678-0100

Nonmetallic Hose Assembly - Page 2 of 2



Thread	<b>Series</b>	Design	nator:

Unf 1st end

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0