Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-678-3101

| Cross Sectional Shape:   |
|--|
| Round  |
| Thread Class:  |
| 2a 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.125 inches   |
| Tempurature Rating:  |
| -65.0 degrees fahrenheit single response   |
| Exterior Color:  |
| Black  |
| Connection Style:  |
| Inverted flare 1st end   |
| End Connection Design:   |
| Straight 1st end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Thready Qty Per Inch (tpi):  |
| 24 1st end   |
| Burst Test Pressure:   |
| 5000.0 pounds per square inch  |
| Layer Composition And Location:  |
| 1st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, chloroprene |
| Maximum Operating Pressure:  |
| 1000.0 pounds per square inch  |
| Thread Size:   |
| 0.375 inches 1st end   |
| Seat Angle:  |
| 42.0 degrees 1st end   |
| Outer Covering Environmental Protection:   |
| Mildew resistant and oil resistant and oil resistant and corrosion resistant                                 |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 13.750 inches  |
| Media For Which Designed:  |
| Brake fluid, nonmineral oil single response  |
| Thread Series Designator:  |
| Unf 1st end  |
|  |
| Shelf Life:  |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-13719 spec.