NSN 4720-00-678-3102

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-678-3102

| Cross Sectional Shape: |
|--|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| |
| Right-hand 1st end Inside Diameter: |
| 0.250 inches |
| |
| Tempurature Rating: |
| 40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.500 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Burst Test Pressure: |
| 5000.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer braided fabric and 2nd layer braided fabric and outer layer molded rubber, chloroprene |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 0.375 inches 1st end |
| Seat Angle: |
| 45.0 degrees 1st end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 11.400 inches |
| Special Features: |
| Reusable end fittings |
| Thread Series Designator: |
| Unf 2nd end |
| Specification Data: |
| 81349-mil-h-13444 government specification |
| Specification Or Standard: |

1 size

NSN 4720-00-678-3102

Nonmetallic Hose Assembly - Page 2 of 2



| _ | | | • | | |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
| | | | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0