## NSN 4720-00-678-6125

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-678-6125

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.750 inches
Minimum Inside Bending Radius:
1.750 inches
Connection Style:
Inverted flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
1st layer braided synthetic cord and 2nd layer braided synthetic cord and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
225.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
30.0 degrees 1st end
Outer Covering Environmental Protection:
Abrasion resistant and cold resistant and oil resistant and ozone resistant
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth
Measuring Method And Length:
24.000 inches
Media For Which Designed:
Air single response
Thread Series Designator:
Nptf 1st end
Shelf Life:

N/a

## NSN 4720-00-678-6125

Nonmetallic Hose Assembly - Page 2 of 2



ı	In	it I	Of	· M	دما	e i	ıre:
ι	JΝ	II '	ωı	IV	еа	SU	ıre:

--

Demilitarization:

No

Fiig:

A542a0