Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-679-0923

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
nside Diameter:
).375 inches
Fempurature Rating:
40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response
Dutside Diameter:
0.750 inches
Ainimum Inside Bending Radius:
.750 inches
Exterior Color:
Black
Connection Style:
nverted flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
000.0 pounds per square inch
ayer Composition And Location:
st layer braided textile yarn and 2nd layer braided textile yarn and outer layer molded rubber, chloropren
Maximum Operating Pressure:
225.0 pounds per square inch
Thread Size:
0.500 inches 1st end
Seat Angle:
30.0 degrees 1st end
lydrostatic Test Pressure:
- I50.0 pounds per square inch
Duter Covering Environmental Protection:
Abrasion resistant and hydraulic solution resistant and ozone resistant and cold resistant
/acuum In Torr:
50.8
nside Surface Condition:
Smooth
Measuring Method And Length:
69.750 inches
Media For Which Designed:
Air single response

Nonmetallic Hose Assembly - Page 2 of 2

AeroBase Group

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0