NSN 4720-00-684-3580

Nonmetallic Hose Assembly - Page 1 of 2

Fuel/oil, hydrocarbon and hydraulic fluid single response



View Online at https://aerobasegroup.com/nsn/4720-00-684-3580

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
Between 0.219 inches and 0.234 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 150.0 degrees fahrenheit single response
Outside Diameter:
Between 0.625 inches and 0.641 inches
Minimum Inside Bending Radius:
3.500 inches
Exterior Color:
Blue or black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Elbow 1st end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer braided steel wire and outer layer molded rubber, chloroprene
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
8000.0 pounds per square inch
Flow Angle:
90.0 degrees 1st end
Inside Surface Condition:
Smooth
Measuring Method And Length:
18.125 inches and 19.438 inches
Media For Which Designed:

NSN 4720-00-684-3580

Nonmetallic Hose Assembly - Page 2 of 2



Thread	Series	Desi	ignator:
--------	--------	------	----------

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0